

The Actor 7-24Vdc communicates wirelessly (bidirectional) at 868MHz and is mainly used for the following applications:

- Electronic Gates
- Hardware link external systems

The Actor7-24Vdc contains one 5Ampere potential free relay.

From the Kadex Pro Server, the product is automatically checked for signal strength and correct functioning.

Scope of delivery:

- Actor 7-24Vdc
- Housing



### ACTOR 7-24V<sub>DC</sub> VERSIONS

Article Number	Model
210609503	Actor 7-24Vdc 1 Channel

## TECHNICAL DATA

<b>Measurements</b>	50 x 50 x 27 mm
<b>Housing</b>	Polyethylene
<b>Color</b>	White
<b>Weight</b>	45 Gram
<b>Protection Class</b>	IP20
<b>Operating Frequency</b>	868 MHz
<b>RF Transmitting Power</b>	Max. 13 dBi (20mW)
<b>Voltage</b>	7V-24Vdc
<b>Usage</b>	Min. 0.2W standby Max. 2.5W
<b>Antenna</b>	Integrated
<b>LED</b>	1x feedback LED

<b>Temperature</b>	
<b>Operational</b>	-10 °C up to 45 °C
<b>Storage</b>	-20 °C up to 70 °C
<b>Relative Air Humidity</b>	90% at 25 °C
<b>Standard Conformity</b>	
<b>Radio Approval</b>	EN300 220-1
<b>EMC - R&amp;TTE</b>	EN301 489-3
<b>Safety</b>	EN 60950-1
<b>Environment</b>	RoHS / WEEE