

Pull Switch

The **Kadex®** Pull Switch is a battery-powered alarm device which communicates wirelessly.

The Pull Switch can be flush mounted on a U50 wall box or surface mounted by using the Kadex surface mount bracket.

Software updates and upgrades can be installed remotely (FOTA) from the Kadex Pro Server. The Kadex Pro Server automatically checks the product for correct operation such as; operation, battery voltage and signal strength.



VARIATIONS

Pull Switch Surface Mount	219953500-A
Pull Switch Flush Mount	219953500-N
Pull Switch Surface Mount With Safety Break Cord	219953507-A
Pull Switch Flush Mount With Safety Break Cord	219953507-N

General Information

Housing	ABS
Colour	White
Weight	111 gram
Protection class	IP 41
Operation Frequency	868MHz 2.4 Ghz*
Power supply	1 x 3.6V Battery, SAFT LS14500
Typical battery life	>3 years
Supported gateways	Kadex Master Locator
Antennas	Integrated
Interface	1 x Pull Switch Program/ reset button
Feedback	Buzzer & RGB LED
Measurements	83 x 83 x 43 mm
Temperature range	
Operation	-10 °C up to 40 °C
Storage	-20 °C up to 70 °C
Relative air humidity	90% at 25 °C
Relative air humidity	90% at 25 °C

CE conformity according to directive 2014/53/EU (RED)

Radio	EN 300 220-2 V3.2.1
EMC	EN 301 489-3:V2.1.1
Safety	EN 62368-1:2014 + A11:2017
Health	EN 62479:2010
Environment	RoHS (III) Directive 2015/863/EU

* Valid for item

Scope of delivery:
- Pull Switch
- Battery